Siena Tiny

DOWNLIGHT




Product Code

MD60

Technical Description

Low glare with adjustable adaptability

- Part of the Siena family: trim Ø143mm, cut-out Ø135mm, 13W - 28W
- Various beam angle options: 12°, 20°, 40°, 60°
- Supports both natural white and warmer optics 3000K, 3000K Vivid, 3500K, 4000K
- Excellent heat management with die cast aluminium housing



Electrical Specifications

System Power	13W, 19W, 28W
Input Voltage	240V
Control Type	Non-Dimmable, DALI Dimmable
System Efficacy (max.)	115lm/W

Photometric Info


Luminaire Lumens	1500lm, 950lm, 2100lm, 1350lm, 2900lm, 1850lm
CRI	CRI90
CCT	3000K, 3000K Vivid, 3500K, 4000K
Beam Angle	12°, 20°, 40°, 60°

Physical Characteristics


Installation Method	Adjustable Recessed
Trim Finish	White, Black
IP Rating / IK Rating	IP20
Weight	1kgKgs
Diffuser	Clear
Maximum Tilt Angle	70°
Maximum Rotation Angle	350°

Polar Distribution Diagrams


Siena Tiny 60°



Siena Tiny 15°



Siena Tiny 24°



Siena Tiny

DOWNLIGHT

Siena Tiny 40°

